

EDGE™ 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, Low-Loss, LC UPC Uniboot to LC UPC Uniboot, 5 m

CORNING

Part Number:
E787802GNZ20005M

Corning® SMF-28® Ultra single-mode fibres combine industry-leading attenuation and improved macrobend performance. As the industry's leading supplier of fibre, our state-of-the-art manufacturing process for cable assemblies ensures unsurpassed fibre and connector performance that meets and exceeds industry standards for connector reflectance and insertion loss. Low-loss connectivity enables system design flexibility for your application.

Features and Benefits

State-Of-The-Art Manufacturing Processes

Corning proprietary manufacturing processes and advanced technology result in unsurpassed product consistency

Global operations


Worldwide manufacturing facilities and end-to-end vertical integration across the entire process ensure reliable supply and mitigate trade barriers or supply disruptions

Flexible design options

Choice of materials for strength elements and fibre properties dependent on application requirements

Superior Performance Testing

Every termination is tested to ensure the highest in network performance



EDGE™ 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, Low-Loss, LC UPC Uniboot to LC UPC Uniboot, 5 m



Specifications

General Specifications	
Flame rating	LSZH/FRNC
Fibre category	Single-mode (OS2)
Product category	Core product / Fastship
Cable assembly type	Patch cords
Environment	Indoor
Application	Data Centre
Cable Type	Tight-buffered
Brand	EDGE™

Standards	
Reaction to Fire	Dca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Intermateability	IEC 61754

Environmental Conditions	
Temperature range, installation	-10 °C to 60 °C
Temperature range, operation	-10 °C to 60 °C
Temperature range, storage	-10 °C to 60 °C

Design	
Fibre count	2
Outer jacket material	LSZH/FRNC
Outer jacket colour	Yellow
Polarity	Crossed, TIA-568 Type-B

EDGE™ 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, Low-Loss, LC UPC Uniboot to LC UPC Uniboot, 5 m



Mechanical Characteristics	
Fire load	0.3 MJ/m
Minimum bend radius	10 mm
Tensile strength	150 N
Nominal outer diameter	2 mm
Crush resistance	1000 N/10 cm
Min. bend radius installation	20 mm
Min. bend radius operation	10 mm

Optical Characteristics	
Fibre code	Z
Performance option code	25
Fibre category	OS2
Fibre Type	Single-mode (OS2) / 250 µm
Fibre name	Bend-Improved Single-mode (OS2)
Maximum Attenuation	0.38 dB/km / 0.38 dB/km / 0.25 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre compliance	ITU-T G.652.D and ITU-T G.657.A1
Fibre core diameter	8.2 µm
Cladding diameter	125 µm
Coating diameter	242 µm
Dispersion @ 1550 nm	≤ 18 [ps/(nm*km)]
Dispersion @ 1625 nm	≤ 22 [ps/(nm*km)]
Cable cutoff wavelength	1260 nm
Mode-Field Diameter at 1310 nm	9.2 µm
Mode-Field Diameter at 1550 nm	10.4 µm
PMD Link Design Value	≤ 0.04 ps/√km
PMD (Polarization Mode Dispersion) maximum individual fibre	≤ 0.1 ps/√km

EDGE™ 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, Low-Loss, LC UPC Uniboot to LC UPC Uniboot, 5 m



Specifications - Connector A	
Reflectance, typical	≤ -58 dB
Polish	UPC
Insertion loss, typical	0.1 dB
Insertion loss, max.	0.15 dB
Tensile strength jacketed cable	50 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot colour	Blue
Connector type	LC UPC uniboot
Ferrule material	Ceramic
Housing colour	Blue
Housing material	Composite
Boot type	Uniboot
Reflectance	≤ -40 dB

Specifications - Connector B	
Reflectance, typical	≤ -58 dB
Polish	UPC
Insertion loss, typical	0.1 dB
Insertion loss, max.	0.15 dB
Tensile strength jacketed cable	50 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot colour	Blue
Connector type	LC UPC uniboot
Ferrule material	Ceramic
Housing colour	Blue
Housing material	Composite
Boot type	Uniboot

EDGE™ 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, Low-Loss, LC UPC Uniboot to LC UPC Uniboot, 5 m



Specifications - Connector B

Reflectance	≤ -40 dB
-------------	----------

Dimensions

Length	5 m
Outer diameter	2 mm
Weight	0.03 kg

Ordering Information

Product Number	E787802GNZ20005M
EAN Code	4042673630432
Packaging method	Box
Units per delivery	1/1
Shipping Height	190 mm
Shipping Width	250 mm
Shipping Depth	380 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.