

ALTOS® Loose Tube Steel Armor Outdoor Cable LT 2.3 4x12 E9 SMF-28e+® ITU G652.D

CORNING

Part Number:
048ERC-T3122A20

Corning stranded loose tube cables with smooth steel tape armoring is designed for outdoor use for campus, city and intercity backbones in duct and direct burial installations. The loose tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The buffer tubes and fibers in each tube are color coded for quick and easy identification. The SZ-stranded construction further reduces installation and environmental influences on the transmission parameters and allows mid-span access. These cables are designed for installation in conduits, ducts, and for direct burial.

Features and Benefits

Waterblocking technology

OSP (outdoor) applications

Corrugated steel armoring

Rodent, mechanical protection and direct buried applications

UV- and microbe-resistant

Can be installed in ducts or conduits

Dry cable core by means of water swellable elements

Allows efficient and craft-friendly cable preparation in outdoor applications

Fibres/buffer tubes colour coded to Telcordia-Bellcore

Easy identification of the individual tubes and fibres

SZ-stranded, loose tube design

Isolates fibers from installation and environmental rigors and facilitates mid-span access



ALTOS® Loose Tube Steel Armor Outdoor Cable LT 2.3 4x12 E9 SMF-28e+® ITU G652.D

CORNING

Specifications

General Specifications

Cable Type	Loose Tube
Environment	Outdoor
Product Type	Corrugated Steel Armor
Fiber Category	Single-mode (OS2)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	A-DQ(ZN)(SR)2Y
Application	Direct Buried, Duct
Cable geometry	Round

Standards

Fiber Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2
-----------------	--

Standards

Fiber Standards	TIA/EIA-492CAAB, IEC 60793-2-50 Type B1.3, ITU-T G.652.D, ISO/IEC 11801 Ed.2.2
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-2 F5

Environmental Conditions

Temperature Range, Installation	-5 °C to 50 °C
Temperature Range, Operation	-30 °C to 70 °C
Temperature Range, Storage	-40 °C to 70 °C

Cable Design

Cable Marking	Meter - Handset - Sine - CORNING - Year -ALTOS (R) A-DQ(ZN)(SR)2Y 4X12 E9 LT 2.3
Central Element	Dielectric

ALTOS® Loose Tube Steel Armor Outdoor Cable

LT 2.3 4x12 E9 SMF-28e+® ITU G652.D

CORNING

Cable Design

Fiber Count	48
Number of Ripcords	2
Outer Jacket Color	Black
Outer Jacket Material	Linear Low Density Polyethylene (LLDPE)
Outer Jacket Nominal Thickness	1.5 mm
Tensile Strength Elements and/or Armoring - Layer 1	Corrugated steel tape armor
Buffer Tube Color	Blue, Orange, Green, Brown
Buffer Tube Diameter	2.25 mm
Central Element Diameter	2.5 mm
Number of Active Tubes	4
Number of Filling Elements	2
Number of Tube Positions	6
Tape	Water-swellable
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Color Code Standards	Telcordia

Mechanical Specifications

Crush Resistance	3000 N/10 cm
Max. Tensile Strength for Installation	2700 N
Min. Bend Radius Installation	230 mm
Min. Bend Radius Operation	175 mm
Nominal Outer Diameter	11.6 mm

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fiber Code	E
Fiber Name	E9/125 SMF28e+®

ALTOS® Loose Tube Steel Armor Outdoor Cable LT 2.3 4x12 E9 SMF-28e+® ITU G652.D

CORNING

Optical Characteristics

Fiber Type	Single-mode
Performance Option Code	22
Fiber Core Diameter	8.2 µm
Maximum Attenuation	0.36 dB/km / 0.36 dB/km / 0.22 dB/km
Serial 1 Gigabit Ethernet	5000 MHz*km / - / -
Serial 10 Gigabit Ethernet	10000 MHz*km / - / 40000 MHz*km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Category	OS2

Dimensions

Cable Weight	127 kg/km
Max. cable length per reel/drum	6000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea