

	<b>MGSWA</b>	<b>MGSWL</b>	<b>MGSW1L</b>
<b>Height (U)</b>	from 4 to 21	from 4 to 18	from 4 to 18
<b>Depth (mm)</b>	350, 500, 600, 700, 800	350, 500, 600	400 500, 600
<b>Perforation for fan 120×120 mm</b>	side walls	roof and bottom	roof and bottom
<b>Perforation shape for Fan</b>	hexagon	hexagon	round
<b>Metal thickness in mm (walls/frame/guides)</b>	1.0/1.0/1.5	0.8/1.0/1.5	0.8/1.5/1.5
<b>Permissible load {kg}</b>	80	50	70
<b>Guide type</b>	S-type	L-type	L-type
<b>Unit marking</b>	yes	no	no
<b>Ground screws M4</b>	yes	no	no
<b>Possibility of installing supports M10</b>	yes	no	no
<b>Powder coating</b>	matte shagreen	shagreen	shagreen
<b>Cable feed from top and bottom</b>	pull-out inputs	cutout for breaking out	cutout for breaking out
<b>Cable feed from back</b>	cut for breaking out	cutout for breaking out	cutout for breaking out
<b>Perforation on frame</b>	side edges	no	no
<b>Perforation roof/bottom</b>	front/bottom	front/bottom	front/bottom
<b>Number of pairs of guides in the set</b>	1	1	1
<b>Compatibility of guides UA-MGSWA-R</b>	yes	yes	yes
<b>Possibility of changing the side of door opening</b>	yes	yes	yes