

Everon™ Copper Datacom Class D Patch Cord, 2xRJ45, Cat.5e, U/UTP LSZH™ AWG 26 gray, 0.5 m

CORNING

Part Number: CCADGE-B1002-A005-C0

The application-neutral Everon™ Copper Datacom category 5e patch cords are unshielded (U/UTP). They are assembled with unshielded RJ45 connectors on each end. The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC), low smoke according to IEC 61034 and flame retardant according to IEC 60332-1. Everon Copper Datacom CCADGE patch cords provide additional latch protection. They are available in various lengths and colors.

Features and Benefits


Application-neutral due to using all four pairs of RJ45 connectors

Additional latch protection

Category 5 / 5e

Supports Power over Ethernet (PoE / PoE+ / PoE++).
IEEE 802.3bt-2018 performance (4PPoE)
Ready for new applications powered on 4 pairs up to 90W

Supports Power over Ethernet (PoE / PoE+) according
IEEE 802.3at



Everon™ Copper Datacom Class D Patch Cord, 2xRJ45, Cat.5e, U/UTP
LSZH™ AWG 26, gray, 0.5 m

Everon™ Copper Datacom Class D Patch Cord, 2xRJ45, Cat.5e, U/UTP LSZH™ AWG 26 gray, 0.5 m

CORNING

Specifications

Cable Design

Outer Jacket Color	Grey
Conductor	Copper Wire, AWG 26
Twisting	2 cores to a pair
Outer Jacket Material	LSZH™/FRNC

Ordering Information

Product Number	CCADGE-B1002-A005-C0
EAN Code	4064394123673
Length	0.5 m
Weight	0.021 kg
Packaging Method	Corn Starch Bag
Shipping Weight	0.027 kg
Units per Delivery	1/1

Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C
Temperature Range, Operation	-20 °C to 60 °C
Transport and Indoor Storage	Dry environment, no direct sunlight, room temperature ≤ 40 °C

General Specifications

Area/Range of Application	10Base-T; 100Base-TX; 1000Base-T/155; 622Mb/sATM
Cable Assembly Type	Patch Cords
Environment	Indoor
Category	5e
Cable Type	U/UTP

Everon™ Copper Datacom Class D Patch Cord, 2xRJ45, Cat.5e, U/UTP LSZH™ AWG 26 gray, 0.5 m

CORNING

General Specifications

Halogen-free	Yes
Legacy Part Number	VOL-5EUDL
Brand	Everon™

Mechanical Specifications

Fire Load	0.303 MJ/m
Min. Bend Radius Installation	34 mm

Electrical Specifications

Mutual capacity	1600 pF/km
Max. loop resistance	150 Ω/km
Delay skew	45 ns/100 m
Propagation delay	5.38 ns/m at 100 MHz
DC resistance unbalance	5 %
Insulation Resistance	500 MΩ*km
Impedance Zo at 1-100 MHz	100 Ω ± 5% at 100 MHz

Specifications - Connector A

Connector Type	RJ45 - 8/8
Durability Cycles	750 N/A
Connector Material	Pin gold plated 50μ inch

Specifications - Connector B

Connector Type	RJ45 - 8/8
Durability Cycles	750 N/A
Connector Material	Pin gold plated 50μ inch

Everon™ Copper Datacom Class D Patch Cord, 2xRJ45, Cat.5e, U/UTP LSZH™ AWG 26 gray, 0.5 m

CORNING

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Transmission Performance Link	ISO/IEC 11801; EN 50173-1; TIA 568.2-D
Design and Test Criteria	Compliant with PoE / PoE+ IEEE 802.3af & IEEE 802.3at
Halogen content test	Low Smoke to IEC 61034
Level of corrosion	Non-corrosive according to IEC 60754-2
Flame Retardance	Flame retardant according to IEC 60332-1-2 (single cable)



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.