

# FutureCom™ U/UTP 200/24, Category 5e, LSZH™/FRNC, Eca 4P, Green

The CORNING logo is displayed in white, uppercase letters on a dark blue rectangular background.**Part Number:  
UU009120237**

FutureCom™ U/UTP 200/24, LSZH Cable: twisted pair,  
covered by a LSZH jacket, spec. up to 200MHz, AWG  
24, Cat.5e acc. ISO/IEC11801, Eca

## Features and Benefits

U/UTP 200/24 copper cable specified up to 200 MHz

---

Fulfills all requirements of category 5e according to EN  
50288-3-1 and IEC 61156-5

---

Ensures high system margins according ISO/IEC 11801  
Ed.2.2 (2011) and EN 50173-1 series (2011)

---

Twisted pair, covered by a LSZH Jacket CPR Eca

---

Satisfies Class B + interference radiation as well as  
immunity standards (EN 55022 and EN 55024)

---

Supports Power over Ethernet (PoE / PoE+) according  
IEEE 802.3at

# FutureCom™ U/UTP 200/24, Category 5e, LSZH™/FRNC, Eca 4P, Green

CORNING

## Specifications

### Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C
Temperature Range, Operation	-20 °C to 60 °C

### General Specifications

Environment	Indoor
Category	5e
Cable Type	U/UTP
Bandwidth	200 MHz
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	Eca
Legacy Part Number	VOL5EUL4305

### Cable Design

Conductor	Copper Wire, AWG 24
Conductor Insulation	Solid PE
Twisting	2 cores to a pair
Outer Jacket Material	LSZH™
Outer Jacket Color	Green

### Mechanical Specifications

Fire Load	330 MJ/m
Nominal Outer Diameter	4.9 mm
Min. Bend Radius Installation	8x Cable-Ø (over flat side)
Maximum Tensile Strength	80 N

# FutureCom™ U/UTP 200/24, Category 5e, LSZH™/FRNC, Eca 4P, Green

CORNING

## Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 MΩ*km
Propagation delay	534 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Insulation Resistance	5000 MΩ*km
Surface transfer impedance	100 mΩ
Propagation Velocity at >10 MHz (NVP*c)	66 %

## Ordering Information

Product Number	UU009120237
Length	305 m
Weight	28.9 kg
Packing Type	Reelex Box

## Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-3-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, TIA/EIA 568-C.2; IEC 60304
Design and Test Criteria	IEEE 802.3 an 1000 Base-TCompliant with PoE / PoE++ IEEE 802.3af, IEEE 802.3at
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

## Electrical Characteristics

Frequency [MHz]	4	10	20	63	100	200
-----------------	---	----	----	----	-----	-----

# FutureCom™ U/UTP 200/24, Category 5e, LSZH™/FRNC, Eca 4P, Green

CORNING

## Electrical Characteristics

Attenuation according to Standard [db/100m]	4.1	6.5	9.3	17.0	22.0	
Typical attenuation [db/100m]	3.8	6.0	8.5	15.2	19.5	28.0
NEXT according to Standard [db/100m]	56.3	50.3	45.8	38.4	35.3	
Typical NEXT Values [db/100m]	63.0	57.0	52.0	45.0	42.0	37.0
ACR-N according to Standard [db/100m]	52.2	43.8	36.5	21.4	13.3	
Typical ACR-N Values [db/100m]	59.2	51.0	43.5	29.8	22.5	9.0



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.