

Central Tube Steel Armour Indoor/Outdoor Cable 1x12 G50 MMF ClearCurve® OM4 CT 3.0



Part Number:
012TEY-13198H2G

Corning MPC (multipurpose cable) central tube cables with corrugated steel armoring are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct, direct burial and riser applications. The central tube cable construction, by isolating the fibres from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibres are color coded for quick, easy identification. Based on a central buffer tube, the cable construction is compact, light, flexible and ideal for connections requiring a moderate fibre count. The cables are designed for installation in conduits, ducts, direct burial and in-house.

Features and Benefits

Waterblocking technology

OSP (outdoor) applications

UV- and microbe-resistant

Can be installed in ducts or conduits

Corrugated steel armoring

Rodent, mechanical protection and direct buried applications

Small diameter and bend radius


Easy installation in space-constrained areas

Fibres colour coding to Telcordia-Bellcore

Easy identification of the individual fibres

Flame retardant

LSZH/FRNC



Central Tube Steel Armour Indoor/Outdoor Cable 1x12 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Specifications

General Specifications

Installation Methods	Direct Buried, Duct, Horizontal, Riser
Cable type	Central Tube
Environment	Indoor/Outdoor
Product type	Corrugated steel armour
Fibre category	50 µm MM (OM4)
Flame rating	LSZH/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)(SR)H
Cable geometry	Round

Standards

Reaction to Fire	Eca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-22 Method F5B
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Reaction to Fire Requirements	Reaction to fire according to EN 50575 and EN 13501-6

Environmental Conditions

Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-30 °C to 75 °C
Temperature range, storage	-40 °C to 75 °C
Temperature range, storage (stored on drum with original packing)	-40 °C to 75 °C

Cable Design

Cable marking	Metre - Handset - Sine - CORNING - Fiber Optic Cable - Year - U-DQ(ZN)(SR)H 12 OM4CC CT 3.0 LSZH™/FRNC
Fibre count	12

Central Tube Steel Armour Indoor/Outdoor Cable 1x12 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Cable Design

Number of ripcords	2
Outer jacket colour	Black
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	1.5 mm
Tensile strength elements and/or armouring - Layer 1	Aramid yarn with swellable elements
Buffer tube diameter	3 mm
Buffer tube water blocking	Thixotropic gel
Fibre colouring	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise
Fibres per tube	12

Mechanical Specifications

Crush resistance	2000 N/10 cm
Max. tensile strength for installation	1000 N
Min. bend radius installation	150 mm
Min. bend radius operation	110 mm
Nominal outer diameter	7.5 mm

Optical Characteristics

Fibre code	T
Performance option code	98
Fibre category	OM4
Fibre Type	Multimode
Fibre name	50 µm MM (OM4)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fibre compliance	IEC 60793-2-10
Fibre core diameter	50 µm

Central Tube Steel Armour Indoor/Outdoor Cable 1x12 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Optical Characteristics

Cladding diameter	125 µm
Coating diameter	242 µm
Serial 1 gigabit ethernet	1000 m / 600 m
Serial 10 gigabit ethernet	550 m / -
Minimum effective modal bandwidth (EMB)	4700 MHz*km / -
Min. overfilled launch (OFL) bandwidth	3500 MHz*km / 500 MHz*km

Dimensions

Cable Weight	76 kg/km
Max. cable length per reel/drum	4000 m



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.